


## Grade 43 High Test Chain

Grade 43 is a medium carbon steel that has been formed into links and electronically welded. Designed for applications such as wrecking chain, boomer chain and other areas requiring higher strength-to-weight ratios than Proof Coil (Grade 30). Manufactured to ASTM 80 short link specs.

**NOT Approved For Overhead Lifting**



Hallmarked: SCC-4, SX-4 or S4 every 12 inches

### G43 High Test Chain (Full drum)

| STOCK #      |                | Trade size |      | Wire dia.<br>(Inches) | Inside link dimension |      | Feet per drum | Lbs per 100/ft | Working load limit |        |
|--------------|----------------|------------|------|-----------------------|-----------------------|------|---------------|----------------|--------------------|--------|
| SELF COLORED | HOT GALVANIZED | (Inches)   | (mm) |                       | A                     | B    |               |                | (Lbs.)             | (Kgs.) |
| H0216-0400   | H0216-0415     | 1/4        | 7.0  | 0.281                 | 0.98                  | 0.41 | 800           | 75             | 2,600              | 1,180  |
| H0216-0500   | H0216-0515     | 5/16       | 8.0  | 0.343                 | 1.10                  | 0.48 | 550           | 115            | 3,900              | 1,770  |
| H0216-0600   | H0216-0615     | 3/8        | 10.0 | 0.406                 | 1.34                  | 0.57 | 400           | 160            | 5,400              | 2,450  |
| H0216-0800   | H0216-0815     | 1/2        | 13.5 | 0.531                 | 1.50                  | 0.75 | 200           | 270            | 9,200              | 4,174  |

◆ Design factor 3:1

Order unit: Full drum



### G43 High Test Chain (Half drum)

| STOCK #      | Trade size | Wire dia. | Inside link dimension |      | Feet per | Lbs per | Working load limit |        |
|--------------|------------|-----------|-----------------------|------|----------|---------|--------------------|--------|
| SELF COLORED | (Inches)   | (Inches)  | A                     | B    | 1/2 drum | 100/ft  | (Lbs.)             | (Kgs.) |
| H0214-0400   | 1/4        | 7.0       | 0.98                  | 0.41 | 400      | 75      | 2,600              | 1,180  |
| H0214-0500   | 5/16       | 8.0       | 1.10                  | 0.48 | 275      | 115     | 3,900              | 1,770  |
| H0214-0600   | 3/8        | 10.0      | 1.34                  | 0.57 | 200      | 160     | 5,400              | 2,450  |
| H0214-0800   | 1/2        | 13.5      | 1.50                  | 0.75 | 100      | 270     | 9,200              | 4,174  |

◆ Design factor 3:1

Order unit: Half drum



### G43 High Test Chain (5 Gallon pail)

| STOCK #      |             | Trade size |      | Wire dia.<br>(Inches) | Inside link dimension |      | Feet per pail | Lbs per pail | Working load limit |        |
|--------------|-------------|------------|------|-----------------------|-----------------------|------|---------------|--------------|--------------------|--------|
| SELF COLORED | BRIGHT ZINC | (Inches)   | (mm) |                       | A                     | B    |               |              | (Lbs.)             | (Kgs.) |
| H0210-0405   | H0210-0411  | 1/4        | 7.0  | 0.281                 | 0.98                  | 0.41 | 150           | 105          | 2,600              | 1,180  |
| H0210-0505   | H0210-0511  | 5/16       | 8.0  | 0.343                 | 1.10                  | 0.48 | 100           | 119          | 3,900              | 1,770  |
| H0210-0605   | H0210-0611  | 3/8        | 10.0 | 0.406                 | 1.34                  | 0.57 | 75            | 124          | 5,400              | 2,450  |
| H0210-0805   | -           | 1/2        | 13.5 | 0.531                 | 1.50                  | 0.75 | 40            | 114          | 9,200              | 4,174  |

◆ Design factor 3:1

Order unit: Pail



**WARNING:** Do not exceed the Working Load Limit. Do not use if chain links or component parts are visibly worn, damaged or distorted. **▲ This chain is NOT designed or approved for overhead lifting. Only G80 Alloy (S-8) chain is approved for overhead lifting.**